



PREMIX PLASTER

August 2021

Product Data Sheet

GENERAL DESCRIPTION

QuickMix Premix Plaster is a versatile pre-mixed mortar, specially designed for plastering and repair works.

APPLICATIONS

- Brick wall plastering only.
- Patching and surface improvement works.
- Suitable to be used for internal and external applications.



ADVANTAGES

- Easy to mix and apply.
- High adhesion and strong bond.
- Durable and weather resistant.
- Versatile mortar for plastering and repair works
- Comes pre-mixed for good and consistent quality.

PRODUCT INFORMATION

Appearance	Grey
Binder	Ordinary Portland Cement
Packaging	1 kg
Shelf Life	6 months from date of manufacture



PREMIX PLASTER

August 2021

Product Data Sheet

TECHNICAL INFORMATION

28 Days	
Tensile Adhesion (BS EN 1015-12)	≥ 0.5 N/mm ²
Compressive Strength (BS EN 1015-11)	≥ 6.0 N/mm ²
Applicable Thickness	Plastering : 20 - 25mm
Recommended Thickness	Plastering : 10 - 12mm / layer

Note: The values given are average figures achieved in laboratory conditions at 20°C.

APPLICATION GUIDE

SURFACE PREPARATION

1. Surface must be clean, free from dust, oil, and any trace of foreign materials as it may affect bonding.
2. Patch up all defects on the surface before plastering.
3. For dry or highly absorbent wall surface, moisten it with water before application.
4. Ensure the surface is wet before applying QuickMix DIY Premix Plaster.

MIXING

1. Mix 1kg of QuickMix DIY Premix Plaster with 150 - 300ml of water and mix thoroughly with a trowel for 3 - 5 minutes until a homogeneous paste is formed.
2. Ensure the mix is smooth and has no lumps before using.
3. Mix paste for 1 minute before application if left unused for more than 15 minutes.



PREMIX PLASTER

August 2021

Product Data Sheet

APPLICATION

(A) PLASTERING

1. QuickMix DIY Premix Plaster is best applied onto the surface with a steel brick trowel.
2. If application requires a few layers, the layers underneath must be dry before applying the next layers.

(B) PATCHING

1. QuickMix DIY Premix Plaster is applied onto the damaged surface with a steel brick trowel.



*Application Step 1:
Apply on steel brick trowel*

PACKAGING

QuickMix DIY Premix Plaster is packed in a 1kg box.

STORAGE & SHELF LIFE

QuickMix DIY Premix Plaster in its original packing, when stored in a covered dry place that is free from excessive moisture, has a shelf life of 6 months from its date of manufacture. Customers are encouraged to use the product promptly to avoid the possibility of storage-related contamination. This product may contain some minor defects as a result of manufacturing and/or processing. Durability of the product varies depending on your usage of the product.

HEALTH & SAFETY

QuickMix DIY Premix Plaster is non-hazardous. However, it may cause skin irritation. It is recommended that users wear appropriate safety equipment when handling this product including PVC gloves, dust masks, full eye protection, and boots, where necessary. In case of contact with eyes, wash immediately and thoroughly with plenty of clean water. If irritation persists, seek immediate medical attention.

Disclaimer: All information provided for herein, which includes without limitation the suggestions for use and application of the product, are only intended to give a general description of the product based on information obtained from laboratory tests and practical experience. The information provided herein does not in any way constitute a warranty by us and is not a guarantee of its accuracy or completeness in describing the nature, performance or suitability of the product. We shall not be responsible for any damage, expense, liability, loss, claim, demand, action, suit or proceedings whatsoever whether arising at common law or by statute caused by the use, application and/or storage of the product and/or the information provided herein (as the case may be), which includes without limitation any personal injury to, or death of, any person whomsoever and loss, injury, of or damage of any kind to any property, whether real or personal. It is the user's responsibility to satisfy himself / herself as to the suitability of information provided herein for their intended use. We reserve the right to alter the given data without prior notice.

For further information and advice, please contact us directly via the details below

LAFARGE DRYMIX SDN BHD [198401002422 (114938-T)
Level 13, Menara YTL, 205, Jalan Bukit Bintang, 55100 Kuala Lumpur, Malaysia.
Tel : +603-2038 0800 Website: www.ytlcement.com

